



# MAXIM PERIPHERALS PVT. LTD.

## Panel Printer PNP-64



**PNP-64**

### SPECIFICATION FOR THE PNP-64 PANEL PRINTER

<b>Printing Method</b>	:	Direct Thermal Printing.
<b>Print Width</b>	:	48 mm
<b>Print Speed</b>	:	Option 1 : 2 lines/sec (5VDC) Option 2 : 12 Lines/sec (8.5VDC)
<b>Resolution</b>	:	203 DPI (8 dots/mm)
<b>Paper Loading</b>	:	Easy 'Clam Shell' type
<b>Characters per line</b>	:	29 (default) or 42
<b>Character set</b>	:	96 Characters ASCII (As shown below) : !"£\$%&'( ) * + , - . / 0 1 2 3 4 5 6 7 8 9 : ; < = > ? @ A B C D E F G H I J K L M N O P Q R S T U V W X Y Z [ \ ] ^ _ ` a b c d e f h i j k l m n o p q r s t u v w x y z ° # ~
<b>Fonts</b>	:	Normal, Double Width, Double Height & Quadruple Size
<b>Sensors</b>	:	'No Paper' sensor
<b>Paper Type</b>	:	Direct Thermal Paper
<b>Paper Roll</b>	:	Width 58mm. Outer Diameter 40mm
<b>Reliability</b>	:	MCBF 50 km
<b>Interface</b>	:	RS-232C
<b>Data Buffer</b>	:	768 Characters
<b>Power</b>	:	Option 1 : 5VDC @ 1.5A (Peak 3A) Option 2 : Logic 5VDC @ 250mA Mechanism 8.5 VDC @ 1.5A (Peak 3A)
<b>Cutter</b>	:	Manual
<b>Dimensions</b>	:	External 80(W) x 76(L) x 43(H) mm Panel Cut-out 76.2 x 72mm