

# Thermal Mobile Printer **MOB-81**



Retail



Hospitality



Healthcare




Finance



Print receipts  
***'On The Go!'***

# Thermal Mobile Printer MOB-81




**Supercharges your busy staff with industry leading battery life of up to 10 hours.**



**Weights just 200 gm and fits perfectly in your palm.**



**Easy paper loading ensures easy paper changes, even on the go.**



**Stress-free, wider data reading. Thanks to the spacious 3 inch paper width.**



|                        |   |
|------------------------|---|
| Printing method        | Direct thermal  |
| Printing speed         | 50 mm/sec   |
| Paper width            | 79.5 ±0.5 mm  |
| Diameter of paper roll | <40 mm  |
| Paper thickness        | 0.06-0.08 mm  |
| Character size         | ANK, Font A : 12 x 24 dots • Font B : 9 x 17 dots<br>Simplified / traditional Chinese : 24 x 24 dots  |
| Column capacity        | 576 mm dots / line (58 mm)  |
| Line spacing           | 3.75 mm (changeable using commands)   |
| Interface              | Bluetooth + USB + serial  |
| Barcode                | 1D barcode : UPC-A/UPC-E / JAN13(EAQN13) / JAN8(EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128<br>2D barcode : QR CODE / PDF417  |
| Extended characters    | PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran (WPC1252), PC866 (Cyrillic#2), PC852 (Latin2), PC858 (Iran, Latvian, Arabic), PT151(1251) |
| NV flash               | 64 KBytes   |
| Input buffer           | 32 KBytes   |
| Power supply           | Input : AC 110V/240, 50-60Hz<br>Output : AC 9.5V 1A   |
| Battery                | 2000 mAh  |
| Reliability            | Printing head life 50 km  |
| Working environment    | Temperature : 0 - 45°C<br>Humidity : 10%-80%  |
| Storage environment    | Temperature : -10 - 60°C<br>Humidity : 10%-90%  |
| Drivers                | Win 9X / Win 2000 / Win 2003 / Win XP / Win 7 / Win 8 / Win 8.1 / Linux / IOS / Android   |
| Command                | Compatible with ESC/POS   |
| Gross weight           | 0.21 kg   |
| Dimension              | 108.5 x 105 x 48 mm   |